

FDNP.MH59962 - DRINKING WATER SYSTEM COMPONENTS

Drinking Water System Components

See General Information for Drinking Water System Components

SIGELock SYSTEMS L L C
3205 Lawson Blvd
Oceanside, NY 11572 USA

MH59962

NSF/ANSI 61

Plant at: Franklin, PA

Mechanical Devices

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl	Surface Area to Volume Ratio
Fire Hydrants			
Spartan, Flanged Joint, 5-1/4 inch base valve size, 300 psig [Annex G]	23	Multiple	-
Spartan, Mechanical Joint, 5-1/4 inch base valve size, 300 psig [Annex G]	23	Multiple	-
Spartan, Plain End with Integral Gland, 5-1/4 inch base valve size, 300 psig [Annex G]	23	Multiple	-
Spartan, Tyton Joint, 5-1/4 inch base valve size, 300 psig [Annex G]	23	Multiple	-

[Annex G] - Product is certified to NSF/ANSI 372 and conforms to the lead content requirements for "lead free" plumbing as defined by California, Louisiana, Maryland and Vermont state law, and the U.S. Safe Drinking Water Act.

Last Updated on 2019-03-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"